

	FULL COMPATIBILITY	LIMITED COMPATIBILITY	NON-COMPATIBILITY
MATERIAL COMPOSITION (TOTAL AMOUNT OF PP & AMOUNT OF PE ATTACHMENTS IN THE PACKAGING)	A >= 95%, B >= 80% and all packaging features are FULLY compatible with recycling	C >= 70% and all packaging features are FULLY compatible with recycling	Non-recyclable < 70 % and all packaging features are FULLY compatible with recycling
DESCRIPTION (TEST PROTOCOL)	Materials that passed the testing protocols with no negative impact**** OR materials that have not been tested (yet), but are known to be acceptable in PP recycling	Materials that passed the testing protocols if certain conditions are met**** OR materials that have not been tested (yet), but pose a low risk of interfering with PP recycling	Materials that failed the testing protocols OR materials that have not been tested (yet), but pose a high risk of interfering with PP recycling
DESCRIPTION (METHODOLOGY)	In case of at least one limited compatibility one penalty is applied, lowering the recyclability class from A to B or from B to C	In case of at least one limited compatibility one penalty is applied, lowering the recyclability class from C to non-recyclable	Non-recyclable
MAIN BODY	MATERIAL*	Multilayer PP/PE with PE <= 10 %	Any other polymer (ex. PET, PVC, etc.)
	COLOURS	Light colours; translucent colours	Dark colours; black; carbon black
	SIZE	<a href="#">Packaging surface between 30 and 100 cm² (sorting test)</a>	Packaging surface < 30 cm²
	PRODUCT RESIDUES (EASY TO EMPTY INDEX)	C if the index is < 15 %	Index is >= 15 %
	BARRIER	<= 5 % EVOH (in polyolefinic combination film)	> 5 % EVOH (in polyolefinic combination film); Barrier layer PVC, PVDC, PA; <a href="#">AlOx coating with PVOH primer</a> ; any other barrier layer; <a href="#">metallisation</a> ; aluminium
	ADDITIVES		PBT Voiding Agent; Bio-/oxo-/photodegradable additives; foaming agents used as expandant chemical agents; Additives that do increase the density higher than 0,97 g/cm³ (CaCO3, talc, glass fibers, etc.)
	LAMINATING ADHESIVES	<a href="#">Aliphatic polyurethanes between 2.3 % and 4.5 %;</a> <a href="#">Water-based acrylics &lt;= 2.5 %;</a> <a href="#">Laminating adhesives approved as limited compatible by RecyClass;</a> To be tested if in combination with a barrier material other than EVOH	<a href="#">Aliphatic polyurethanes &gt; 4.5 %;</a> <a href="#">Water-based acrylics &gt; 2.5 %;</a> <a href="#">Aromatic polyurethanes;</a> <a href="#">Laminating adhesives specially developed for high thermal applications above boiling and/or for high chemical resistance (to be tested);</a> Any other laminating adhesives
ATTACHMENTS	CLOSURE SYSTEM	PE	Metal, aluminium, PVC, PET, PETG, PS, PLA, non PO or foams with density < 1 g/cm³
	LINERS, SEALS AND VALVES	PE, removable aluminium liddings	Metal, aluminium, PVC, PET, PETG, PS, PLA, foiled paper, non PO or foams with density < 1 g/cm³
	OTHER COMPONENTS	PE	Metal, aluminium, PVC, PET, PETG, PS, PLA, paper, foams with density < 1 g/cm³
DECORATION	FACESTOCK LABEL MATERIAL	PE	Metallized labels, any other; paper labels
	ADHESIVES FOR LABELS		Adhesives non-soluble in water or non-releasable in water at less than 40°C
	INKS**	Printing with coverage < 50 %***	Bleeding inks; Inks non-compliant with EuPIA Exclusion Policy; PVC co- and terpolymer binders; Any other chlorinated binders; Printing covering > 50% ***
	OTHER DECORATIVE TECHNOLOGIES	Laser marking with coverage < 50 %***	

**RECYCLED CONTENT:** No change in the recyclability assessment. A separate '[Recycled Plastics Traceability Certification](#)' based on a Chain of Custody approach is available with RecyClass

\* Polymer resin can be either fossil- or bio-based, virgin or recycled.  
 \*\* Nitrocellulose (NC) based inks impact on recyclability is under investigation by RecyClass.  
 \*\*\* Temporary solution  
 \*\*\*\* Approved technologies can be found [here](#)

Last update: July 2025