

Avery Dennison

RECYCLASS TECHNOLOGY APPROVAL

Brussels, 03 December 2021

DISCLAIMER

RecyClass recognition applies only to Avery Dennison 'PP60 TOP WHITE – Acrylic Adhesive, Film Thickness $\leq 60\mu\text{m}$ ' technology reported in Annex I. It, therefore, does not concern to a recyclability assessment of specific packaging using this Pressure-Sensitive-Label.

Any specific packaging using this Pressure-Sensitive Label would need to be tested individually to demonstrate that the system of resin, adjuvants, label, closure, and printing conforms to the RecyClass Recyclability Evaluation Protocol for HDPE containers, and that it is sorted in the HDPE rigid stream at the state-of-art sorting plants in Europe.

Publication of results of testing of this technology MUST clearly include all the conditions listed in the approval letter. Partial reporting of the conditions is forbidden.

Additionally, any change in the formulation of the technology must be communicated to the Technical Committee which will reassess the approval of the technology.

The RecyClass HDPE Technical Committee was requested to carry out an assessment of the technology 'PP60 TOP WHITE – Acrylic Adhesive, Film Thickness $\leq 60\mu\text{m}$ ' by Avery Dennison to verify its impact on the quality of recycled HDPE containers.

The technology is white PP Pressure-Sensitive Labels applied unprinted on a HDPE bottle, without cap. The Pressure-Sensitive Labels is composed by a PP facestock and a general-purpose permanent emulsion acrylic adhesive, covering about 40% of the total surface of the bottle. Adhesive represents about 1,2% of the total weight of the tested bottle.

According to the results that were obtained from the laboratory tests done by the Institut für Kunststofftechnologie und -recycling (IKTR), carried out as per the Recyclability Evaluation Protocol for HDPE containers, 'PP60 TOP WHITE – Acrylic Adhesive, Film Thickness $\leq 60\mu\text{m}$ ' technology is considered to be **limited compatible with coloured HDPE recycling.**

Based on these results, RecyClass certifies that Avery Dennison 'PP60 TOP WHITE – Acrylic Adhesive, Film Thickness $\leq 60\mu\text{m}$ ' technology will have a limited impact on the current European coloured HDPE containers recycling and provided that the full packaging using this Pressure-Sensitive Label is designed under the following conditions:

- a) The packaging is made of PE, with a prevalence of HDPE;

- b) The facestock of the Pressure-Sensitive Label applied on the packaging is made of clear or white PP;
- c) The coverage of the Pressure-Sensitive Labels represents 6,35cm²/g of bottle (equivalent to 40% of the packaging surface here), or less;
- d) The amount of acrylic adhesive represents 1,2% of the total weight of the packaging, or less;
- e) The final density of the packaging is lower than 1 g/cm³;
- f) Any additional components, such as closure system are made of PE preferably clear or white;
- g) Applied printing technology is compatible with recycling; since several printing options are possible, it is the responsibility of the end-user to choose an appropriate combination of inks and printing process to ensure that:
 - i. the inks are non-bleeding;
 - ii. the inks comply with the European Legislation (e.g. Packaging and Packaging Waste Directive on the heavy metal concentration levels) and are EUPIA compliant;
 - iii. printing is limited as much as possible, using preferably light colours.

RecyClass concludes that Avery Dennison ‘PP60 TOP WHITE – Acrylic Adhesive, Film Thickness ≤60µm’ technology as per current market conditions and knowledge, is limited compatible with the existing European industrial recycling processes for coloured HDPE containers. Indeed, the recycled plastic generated after the recycling process was successfully tested in high-value application such as HDPE bottles up to 100% concentration¹.

It should be noteworthy that application of extensive printing on the non-separable Pressure-Sensitive Label reduces the quality of recycled plastic generated by the container, by limiting its compatibility with HDPE recycling. This approval is granted for a period of 2 years, during which the applicant will endeavor to improve the Pressure-Sensitive Label construction to allow its removal during the recycling process, based on RecyClass HDPE Technical Committee recommendation.

About

RecyClass is a comprehensive cross-industry initiative that works to advance plastic packaging recyclability and to establish a harmonized approach towards recycled content calculation and traceability in Europe. Activities within RecyClass include the development of Recyclability Evaluation Protocols and scientific testing of innovative materials which serve as the base for the Design for Recycling guidelines and the free online tool. RecyClass offers Recyclability Certifications and Recycled Content Traceability Certification for plastic packaging.
Contact: Alice.Wallon@plasticsrecyclers.eu, www.recyclass.eu

¹ [Recyclability Evaluation Protocol for HDPE containers](#)

Annex I



PP60 TOP WHITE – Acrylic Adhesive, Film Thickness $\leq 60\mu\text{m}$ by Avery Dennison without cap and unprinted