

c/o Plastics Recyclers Europe Avenue de Broqueville 12 1150 Brussels, Brussels Phone: +32 2 786 39 08 info@recyclass.eu www.recyclass.eu

Bostik

RECYCLASS TECHNOLOGY APPROVAL

Brussels, 15 December 2020 Reviewed: Brussels, 19 December 2023

DISCLAIMER

RecyClass recognition applies only to Bostik 'Bosstik SF10M' technology reported in Annex I. The recyclability assessment therefore does not refer to the testing of a specific packaging using this laminating adhesive. Any specific packaging using this laminating adhesive would need to be tested individually to demonstrate that the system of resin, adjuvants, label, closure, and printing conforms to the RecyClass Recyclability Evaluation Protocol for PE films, and that it is sorted in the PE flexible stream at the state -of-art sorting plants in Europe.

Publication of results of testing of this technology MUST clearly include all the conditions listed in the approval letter. Partial reporting of the conditions is forbidden.

Additionally, any change in the formulation of the technology must be communicated to the Technical Committee which will reassess the approval of the technology.

The RecyClass PO films Technical Committee was requested to carry out an assessment of the technology 'Bostik SF10M' by Bostik to verify its impact on the quality of recycled PE flexible packaging.

The technology is a laminated film consisting of one commercial LDPE-based sealing film and a stiff MDO-PE film, laminated together via a solvent-free aromatic polyurethane based lamination adhesive. Polyurethane lamination adhesive comprising about 1,6% of the innovation film weight.

According to the results that were obtained from the laboratory test performed by Proplast, carried out as per the Recyclability Evaluation Protocol for PE films, the 'Bostik SF10M' technology is considered to be <u>fully compatible with PE flexibles recycling</u>.

Based on these results, RecyClass acknowledges that Bostik 'Bostik SF10M' technology will not have a negative impact on the current European PE flexibles recycling provided the PE flexible packaging using this technology are designed under the following conditions¹:

- a) The density of the laminated film is below 1 g/cm³;
- b) The solvent-free aromatic polyurethane laminating adhesive 'Bostik SF10M' represents 1,6wt% of the toptal weight of the film, or less;
- c) Any components or attachments to the packaging should be preferably made of clear PE;

¹ PE films designed under conditions other than those indicated need to be tested to assess their compliance with Recyclass Recyclability Evaluation Protocol for PE films.

d) Any additional component or features (inks, adhesives, ...) of the packaging must be compliant

with the corresponding RecyClass Design for Recycling Guidelines.

RecyClass concludes that Bostik 'Bostik SF10M' technology as per current market conditions and

knowledge, is fully compatible with the existing European industrial recycling processes for PE flexibles.

The plastic generated by the recycling process may be used in high quality applications such as PE

blown films up to 25%².

In regard to RecyClass Recyclability Certification, the present full compatibility with PE flexibles

recycling approval delivered to 'Bostik SF10M' technology, means that a package based on PE film

containing the 'Bostik SF10M' technology, as mentioned in the aforementioned conditions, will not be

penalised with a Recyclability Class downgrade. Nevertheless, the amount of recyclable PE will impact

the final Recyclability Class obtained during Recyclability Certification and should be kept above 95%

or 90% in the final packaging to maximise chances to get a Recyclability Certificate with a Class A or B,

respectively³. Also, it is noteworthy that the presence of additional packaging features, like inks or

barrier material, could additionally impact the certification process.

About RecyClass

RecyClass is a non-profit, cross-industry initiative advancing recyclability, bringing transparency to the origin of plastic waste and establishing a harmonized approach toward recycled plastic calculation & traceability in Europe. RecyClass develops Recyclability Evaluation Protocols and scientific testing methods for innovative plastic packaging materials which serve as the base for the Design for Recycling Guidelines and the RecyClass Online Tool. RecyClass established Recyclability Certifications

for plastic packaging, Recycling Process Certification and Recycled Plastics Traceability Certification for plastic products.

RecyClass - Plastic Future is Circular

Follow the latest news on RecyClass channels: <u>LinkedIn | Twitter | YouTube</u>

Contact: Jean-Emile.Potaufeux@plasticsrecyclers.eu, www.recyclass.eu

² Technology tested according to the RecyClass <u>Recyclability Evaluation Protocol for PE films</u>

³ RecyClass Recyclability Certification



 clers Europe
 Phone: +32 2 315 24 60

 deville 12
 info@recyclass.eu

 ussels
 www.recyclass.eu

Annex I

PE mono-material laminate		
Substrate 1	MDO-PE 40μ	
Adhesive	1,6%	
Substrate 2	LDPE 50µ	

Figure 1 Bostik SF10M technology by Bostik

