

c/o Plastics Recyclers Europe Avenue de Broqueville 12 1150 Brussels, Brussels Phone: +32 2 786 39 08 info@recyclass.eu www.recyclass.eu

Constantia Flexibles

RECYCLASS TECHNOLOGY APPROVAL

Brussels, September 27, 2019 Reviewed: Brussels, 5 April 2024

## **DISCLAIMER**

RecyClass recognition applies only to Constantia Flexibles 'EcoLam High Plus' technology reported in Annex I. The recyclability assessment therefore does not refer to the testing of a specific packaging using this barrier film. Any specific packaging using this film would need to be tested individually to demonstrate that the system of resin, adjuvants, label, closure, and printing conforms to the RecyClass Recyclability Evaluation Protocol for PE films, and that it is sorted in the PE flexible stream at the state -of-art sorting plants in Europe.

Publication of results of testing of this technology MUST clearly include all the conditions listed in the approval letter. Partial reporting of the conditions is forbidden.

Additionally, any change in the formulation of the technology must be communicated to the Technical Committee which will reassess the approval of the technology.

The RecyClass PO Films Technical Committee was requested to carry out an assessment of the technology 'EcoLam High Plus' by Constantia Flexibles to verify its impact on the quality of recycled PE flexible packaging.

The innovative structure is a PE barrier laminate for reel-fed film and pouch with a functional barrier made by combining 3.6 wt% of EVOH compared to the total weight of the packaging and Al metallization. PP copolymer represented about 4.1 wt% of the packaging. The laminating adhesive used was a solvent-free polyurethane, representing 3.1 wt% of the total weight of the film. The film was tested printed with NC/PU inks representing about 1.6 wt% of the weight of the film.

According to the results that were obtained from the laboratory test performed by Proplast, carried out as per the RecyClass Recyclability Evaluation Protocol for PE films, the 'EcoLam HighPlus' is considered to be <u>limited compatible with PE flexibles recycling</u>.

Based on the results, RecyClass acknowledges that Constantia Flexibles 'EcoLam HighPlus' technology will have a limited impact on the current European PE flexibles recycling provided that PE flexible packaging using this technology are designed only under the following conditions<sup>1</sup>:

- a) The density of the printed film is below 0.97 g/cm<sup>3</sup>;
- b) The EVOH represents 3.6% of the total weight of the film, or less;

<sup>&</sup>lt;sup>1</sup> PE films designed under conditions other than those indicated need to be tested to assess their compliance with Recyclass Recyclability Evaluation Protocol for PE films.

c) The PP copolymer represents 4.1% of the total weight of the film, or less;

d) The laminating adhesive is solvent-free polyurethane and represents 3.1 % of the total weight

of the film, or less;

e) The inks are NC/PU and represent 1.6 % of the total weight of the film, or less;

f) Any components or attachments to the packaging should be preferably made of clear PE;

g) Any additional component or features (inks, adhesives,  $\dots$ ) of the packaging must be compliant

with the corresponding RecyClass Design for Recycling Guidelines.

RecyClass concludes that Constantia Flexibles 'EcoLam HighPlus' technology, as per current market

conditions and knowledge, is limited compatible with the existing European industrial recycling

processes for PE flexibles. The plastic generated by the recycling process may be used in high quality

applications such as PE blown films up to 25%<sup>2</sup>.

In regard to RecyClass Recyclability Certification, the present limited compatibility with PE flexibles

recycling approval delivered to 'EcoLam High Plus' technology, means that a package based on PE film

containing the 'EcoLam High Plus' technology, as mentioned in the aforementioned conditions, will be

penalised with one Recyclability Class downgrade. Nevertheless, the amount of recyclable PE will

impact the final Recyclability Class obtained during Recyclability Certification and should be kept above

90% in the final packaging to maximise chances to get a Recyclability Certificate with a Class C3. Also, it

is noteworthy that the presence of additional packaging features, like inks or decorations, could

additionally impact the certification process.

About RecyClass

RecyClass is a non-profit, cross-industry initiative advancing recyclability, bringing transparency to the origin of plastic waste and establishing a harmonized approach toward recycled plastic calculation & traceability in Europe. RecyClass develops Recyclability Evaluation Protocols and scientific testing methods for innovative plastic packaging materials which serve as the base for the Design for Recycling Guidelines and the RecyClass Online Tool. RecyClass established Recyclability Certifications

for plastic packaging, Recycling Process Certification and Recycled Plastics Traceability Certification for plastic products.

RecvClass - Plastic Future is Circular

Follow the latest news on RecyClass channels: <u>LinkedIn | Twitter | YouTube</u>

Contact: <u>Jean-Emile.Potaufeux@plasticsrecyclers.eu</u>, <u>www.recyclass.eu</u>

<sup>2</sup> Technology tested according to the RecyClass Recyclability Evaluation Protocol for PE films

<sup>3</sup> RecyClass Recyclability Certification

